



Jeu de meules pour égouttoirs avec feuillures à 45° - granits et reconstitués type silestone



Code	Description	Type	Vitesse de rotation	Vitesse D'avance Mm/mn	enlèvement [mm/min]	Prix ht
PB29443	Super Duty $\Phi 91 \times 30 \times 7$ B=50	B	4500	400-800	To Shape	185
PB29504	Metal Bond $\Phi 119$ - 45° F=35 Pos.1	D	4.500-5.500	900-1.000	0,15	250
PB29505	Metal Bond $\Phi 119$ - 45° F=35 Pos.2	E	4.000 - 4.500	1.000	0,1	250
PB29365	FLAT $\Phi 100$ Magnetic #50R	F	1.200-1.500	4.000-6.000	0,1	149
PB29371	FLAT $\Phi 100$ Magnetic #100R	H	1.200-1.500	4.000-6.000	0,1	149
PB29720	45° $\Phi 107$ Magnetic #200R	I	1.000-1.200	800-1.200	0,05	180
PB29557	45° $\Phi 107$ Magnetic #500R	J	1.000-1.200	800-1.200	0,05	180
PB29558	45° $\Phi 107$ Magnetic #1000R	K	1.000-1.200	800-1.200	0,05	180
PB29559	45° $\Phi 107$ Magnetic #2000R	L	1.000-1.200	800-1.200	0,05	180
PB29721	45° $\Phi 107$ Magnetic #3000R	M	1.000-1.200	800-1.200	0,05	180
PB29722	45° $\Phi 100$ Magnetic #LUX	N	1.000	3.000	0,1	195
SL02558	Magn Adaptor - Fitting 1/2" Gas Safety Lock	G	-	-	-	134
SL01050	$\Phi 72$ (3 Holes)	A	-	-	-	54
PB29015	$\Phi 72$ (3 Holes)	C	-	-	-	57